

## WPEQ-405AX

WiFi 6 (802.11ax) 4x4 MU-MIMO

5GHz Single Band Mini PCIe Module



### 802.11ax with MU-MIMO 4x4 Solution

The first WiFi-6 (802.11ax) Qualcomm based AP solution on module formfactor from SparkLAN.

WPEQ-405AX, is based on QCN9074 chipset solution. This is a true enterprise based wireless module that powers 4T4R (4x4) MU-MIMO, in 5Ghz Single band mode, hitting a theoretical speed of up to 4.8Gbps with 160MHz support.

Unlike typical Qualcomm reference design around QCN9074 (PN02.1), WPEQ-405AX shrink the traditional 50mmx50mm M.2 E-Key design to a more popular Mini PCIe Full size formfactor of just 50mm x 30mm, run at 3.3V voltage. Provides a greater versatility to use on more common seen design.

WPEQ-405AX performs both AP and STA functionality with 4 spatial streams, although recommended more for hardware AP applications as it supports 4096-QAM, OFDMA technology, makes it perfect for heavy lifting applications such as Enterprise grade AP, UTM, public & transportation Hotspot, and other industrial capable Access Points.

#### Embedded Application

Applications include Multimedia Router and AP solution., etc.

#### Key Feature

- 5GHz, 4x4 MU-MIMO OFDMA Technology, up to 4804Mbps physical data rate
- Single Band 5GHz 4x4 Wi-Fi 6 (802.11ax)
- 4 spatial streams (4SS)
- Perfect for AP solutions
- Support standard full size Mini PCIe module

**Specification**

<b>Standards</b>	IEEE 802.11ax/ac/a/n (4T4R)
<b>Chipset</b>	Qualcomm Atheros QCN9074
<b>Data Rate</b>	802.11a: 54Mbps 802.11n: MCS0~15 802.11ac: MCS0~9 802.11ax: HE0~11
<b>Operating Frequency</b>	IEEE 802.11ax/ac/a/n ISM Band: 5.150GHz~5.850GHz *Subject to local regulations
<b>Interface</b>	WLAN: PCIe
<b>Form Factor</b>	Mini PCIe
<b>Antenna</b>	4 x IPEX MHF1 connectors
<b>Modulation</b>	Wi-Fi : 802.11n: OFDM (BPSK, QPSK, 16-QAM, 64-QAM) 802.11a: OFDM (BPSK, QPSK, 16-QAM, 64-QAM) 802.11ac: OFDM (BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM) 802.11ax: OFDMA (BPSK, QPSK, DBPSK, DQPSK, 16-QAM, 64-QAM, 256-QAM, 1024-QAM, 4096-QAM )
<b>Power Consumption</b>	TX mode: 1954mA(Max.) RX mode: 819mA(Max.)
<b>Operating Voltage</b>	DC 3.3V
<b>Operating Temperature Range</b>	-20°C ~ +70°C
<b>Storage Temperature Range</b>	-20°C ~ +90°C
<b>Humidity (Non-Condensing)</b>	5%~90% (Operating) 5%~90% (Storing)
<b>Dimension L x W x H (in mm)</b>	50.80mm(±0.15mm) x 29.85mm(±0.15mm) x 9.30mm(±0.3mm)
<b>Weight (g)</b>	14.6g
<b>Driver Support</b>	Linux (Open Source)
<b>Security</b>	64/128-bits WEP, WPA, WPA3, 802.1x

**OUTPUT POWER & SENSITIVITY**
**802.11a (Pre-Chain)**

Data Rate	Tx $\pm$ 2dBm	Rx Sensitivity
54Mbps	17dBm	$\leq$ -76dBm

**802.11n / 5GHz (Pre-Chain)**

	Data Rate	Tx $\pm$ 2dBm (1TX)	Rx Sensitivity
HT20	MCS7	17dBm	$\leq$ -70dBm
	MCS7	17dBm	$\leq$ -68dBm


**802.11ac (Pre-Chain)**

	Data Rate	Tx $\pm$ 2dBm (1TX)	Rx Sensitivity
VHT80	MCS9	16dBm	$\leq$ -62dBm
VHT160	MCS9	16dBm	$\leq$ -60dBm


**802.11ax / 5GHz**

	Data Rate	Tx $\pm$ 2dBm (1TX)	Tx $\pm$ 2dBm (2TX)	Rx Sensitivity
HE20	HE11	15dBm	18dBm	$\leq$ -64dBm
HE40	HE11	15dBm	18dBm	$\leq$ -62dBm
HE80	HE11	15dBm	18dBm	$\leq$ -57dBm
HE160	HE11	15dBm	18dBm	$\leq$ -55 dBm


**Block Diagram**



### Mechanical Dimension (mm)



### MHF1 connector spec.



## Pin Assignment

The following section illustrate signal pin-outs for the module connector.

TOP			
Pin#	Pin Name	Type	Description
1	WAKE#	I/O	Open Drain active Low signal. When the add-in card supports wakeup, this signal is used by the add-in card to request that the system return from a sleep/suspended state to service a function initiated wake event. When the add-in card supports the OBFF mechanism, this signal is used by the system to indicate OBFF or CPU Active State transitions.
3	COEX1	NC	No Connection
5	COEX2	NC	No Connection
7	CLKREQ#	I/O	PCIe clock request
9	GND	G	Ground connections
11	REFCLK-	I	PCIe differential clock input- Negative
13	REFCLK+	I	PCIe differential clock input- Positive
15	GND	G	Ground connections
17	UIM_IC_DM	NC	No Connection
19	UIM_IC_DP	NC	No Connection
21	GND	G	Ground connections
23	PETn0	O	PCIe Transmit data-Negative
25	PETp0	O	PCIe Transmit data-Positive
27	GND	G	Ground connections
29	GND	G	Ground connections
31	PERn0	I	PCIe receive data-Negative
33	PERp0	I	PCIe receive data-Positive
35	GND	G	Ground connections
37	GND	G	Ground connections
39	+3.3Vaux	P	VDD system power supply input
41	+3.3Vaux	P	VDD system power supply input
43	GND	G	Ground connections
45	ANTCTRL2	O	WLAN PCIe L1 transmit output differential signals(optional)
47	ANTCTRL3	O	WLAN PCIe L1 transmit output differential signals(optional)
49	Reserved	I	WLAN PCIe L1 receive input differential signals(optional)
51	W_DISABLE2#	I	WLAN PCIe L1 receive input differential signals(optional)

BOTTOM			
Pin#	Pin Name	Type	Description
2	3.3Vaux	P	VDD system power supply input
4	GND	G	Ground connections
6	1.5V/COEX3	NC	No Connection
8	UIM_PWR	NC	No Connection
10	UIM_DATA	NC	No Connection
12	UIM_CLK	NC	No Connection
14	UIM_RESET	NC	No Connection
16	UIM_SPU	NC	No Connection
18	GND	G	Ground connections
20	W_DISABLE1#	NC	No Connection
22	PERST#	I	PCIe host indication to reset the device. Active low.
24	+3.3Vaux	P	VDD system power supply input
26	GND	G	Ground connections
28	+1.5V/ ANTCTRL0	NC	No Connection
30	SMB_CLK	NC	No Connection
32	SMB_DATA	NC	No Connection
34	GND	G	Ground connections
36	USB_D-	NC	No Connection
38	USB_D+	NC	No Connection
40	GND	G	Ground connections
42	LED_WWAN#	O	LED interface 1
44	LED_WLAN#	O	LED interface 0 for RFA debug
46	LED_WPAN#	NC	No Connection
48	+1.5V/ ANTCTRL1	NC	No Connection
50	GND	G	Ground connections
52	+3.3Vaux	P	VDD system power supply input

**Note: Power (P), Ground (G), Open-Drain (OD), Input (I), Output (O), Do Not Connect (DNC), No Connection (NC)**

## Certification

### Dipole Ant.

- |   |  |
|---|--|
| <input checked="" type="checkbox"/> FCC | <input checked="" type="checkbox"/> CE (RED EN 300 328 V2.2.2 / EN 301 893 V2.1.1) |
| <input checked="" type="checkbox"/> IC  | <input type="checkbox"/> MIC   |
| <input type="checkbox"/> NCC            | <input type="checkbox"/> ASNZS   |

## Ordering Information

Product Name	Part Number	Description
WPEQ-405AX	R9701A90005	11ax/ac/a/n 4T4R WiFi Mini PCIe Module

## Optional Accessory

Product Name	Part Number	Description
AD-103AG	R3410110203	Dipole Antenna, 2dBi 2.4GHz/5GHz, RP-SMA(M) connector
AD-302N	R3410110221	Dipole Antenna, 3dBi/2dBi 2.4G/5GHz, RP-SMA(M) connector
AD-303N	R3410110222	Dipole Antenna, 3dBi/3dBi 2.4G/5GHz, RP-SMA(M) connector
CBIRF-ME150	R3470300023	RF Cable, I-PEX/MHF1 to RP-SMA Female; L:150mm; Coaxial 1.37 Black
CBIRF-ME250	R3470300024	RF Cable, I-PEX/MHF1 to RP-SMA Female; L:250mm; Coaxial 1.37 Black